

Serial No. 10/763,994

Amendment in Resp. to Off. Action of Feb. 16, 2006

UTILITY PATENT

B&D No. JK01244

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A table saw, comprising:

a support including an aperture for extending a circular saw blade therethrough, the support including a workpiece support surface for supporting a workpiece to be cut;

an alignment fence adjustably mounted to the table saw, said alignment fence being configured for positioning the workpiece to be cut with respect to the circular saw blade;

an arbor mounted to the table saw generally opposite the workpiece support surface, said arbor being arranged for adjustably supporting the circular saw blade; and

a kerf intrusion device coupled to the arbor such that the kerf intrusion device is disposed in the kerf formed in a workpiece by operation of the circular saw blade, said kerf intrusion device including a body, a guard attached to the body for partially covering a periphery of the circular saw blade, a first anti-kickback pawl coupled to the body, and a side pressure splitter disposed on the body below the first pawl and at least partially positioned in the kerf formed in the workpiece by operation of the circular saw blade, the side pressure splitter being directed towards the alignment fence,

wherein the kerf intrusion device side pressure splitter is orientated such that the side pressure splitter biases a portion of the workpiece being cut between the kerf intrusion device and the alignment fence into contact with the alignment fence.

Claim 2 (original): The table saw claim 1, wherein a kerf intrusion device is at least one of a riving knife and a backsplitter.

Serial No. 10/763,994

Amendment in Resp. to Off. Action of Feb. 16, 2006

UTILITY PATENT

B&D No. JK01244

Claim 3 (original): The table saw of claim 1, wherein the side pressure splitter is a tab formed unitarily with the kerf intrusion device.

Claim 4 (original): The table saw of claim 1, wherein the side pressure splitter is biased by a spring.

Claim 5 (original): The table saw of claim 1, wherein the side pressure splitter includes a trailing edge configured to engage a workpiece to prevent the workpiece from traveling towards the circular saw blade.

Claim 6 (original): The table saw of claim 1, wherein the side pressure splitter is a flexible strip having a first and a second end, the strip being at least partially connected to the kerf intrusion device proximate the first end and the second end so as to act as a leaf spring.

Claim 7 (currently amended): The table saw of claim 1, ~~further comprising at least one anti-kickback pawl coupled to the kerf intrusion device, said at least one~~ wherein the first anti-kickback pawl being is formed to engage a workpiece being directed toward the alignment fence by the side pressure splitter, if the workpiece moves away from the workpiece support surface.

Claim 8 (original): The table saw of claim 1, further comprising a pair of opposing rails mounted, substantially perpendicular to the portion of the circular saw blade extending through the support, on opposite sides of the support, the rails being constructed for slideably mounting the alignment fence thereto.

Claim 9 (currently amended): A table saw, comprising:

a support including an aperture for extending a circular saw blade therethrough, the support including a workpiece support surface for supporting a workpiece to be cut;

Serial No. 10/763,994

Amendment in Resp. to Off. Action of Feb. 16, 2006

UTILITY PATENT

B&D No. JK01244

an alignment fence adjustably mounted to the table saw substantially parallel with the circular saw blade, said alignment fence being configured for positioning the workpiece to be cut with respect to the circular saw blade;

a beveling arbor mounted to the table saw generally opposite the workpiece support surface, said arbor being arranged for adjustably supporting the circular saw blade; and

a back splitter coupled to the arbor whereby the back splitter bevels with the arbor so that the back splitter is disposed in the kerf formed in a workpiece by operation of the circular saw blade, said back splitter including a body, a guard attached to the body for partially covering a periphery of the circular saw blade, a first anti-kickback pawl coupled to the body, and a side pressure splitter disposed on the body below the first pawl and at least partially positioned in the kerf formed in the workpiece by operation of the circular saw blade, the side pressure splitter being directed towards the alignment fence,

wherein the side pressure splitter is orientated such that the side pressure splitter biases a portion of the workpiece between the back splitter and the alignment fence into contact with the alignment fence.

Claim 10 (original): The table saw of claim 9, wherein the side pressure splitter is a tab formed unitarily with the back splitter.

Claim 11 (original): The table saw of claim 9, wherein the side pressure splitter is biased by a spring.

Claim 12 (original): The table saw of claim 9, wherein the side pressure splitter includes a trailing edge configured to engage a workpiece to prevent the workpiece from traveling towards the circular saw blade.

Serial No. 10/763,994

Amendment in Resp. to Off. Action of Feb. 16, 2006

UTILITY PATENT

B&D No. JK01244

Claim 13 (original): The table saw of claim 9, wherein the side pressure splitter is a flexible strip having a first and a second end, the strip being at least partially connected to the back splitter proximate the first end and the second end so as to act as a leaf spring.

Claim 14 (currently amended): The table saw of claim 9, ~~further comprising at least one anti-kickback pawl coupled to the back splitter, said at least one~~ wherein the first anti-kickback pawl being is formed to engage a workpiece being directed toward the alignment fence by the side pressure splitter, if the workpiece moves away from the workpiece support surface.

Claim 15 (original): The table saw of claim 9, further comprising a pair of opposing rails mounted, substantially perpendicular to the portion of the circular saw blade extending through the support, on opposite sides of the support, the rails being constructed for slideably mounting the alignment fence thereto.

Claims 16-20 (canceled).